

SYSTEMS FOR DRAINAGE OF FLAT ROOFS



Snow catchers TOPWET TW SZM, TW SZM 250x250


BASIC INFORMATION

purpose	catching of a snow layer on the roof membrane from mPVC based foil
material	bottom part – hot-dip galvanised sheet metal 0.55 mm thick with a 0.6 mm PVC layer and anticorrosive treatment, upper part – a mould from hot-galvanised sheet metal 0.55 mm thick with a 0.6 mm PVC layer and anticorrosive treatment
manufacturer	TOPWET s.r.o., náměstí Viléma Mrštíka 62, 664 81 Ostrovačice, Czech Republic

EXAMPLE OF LAYOUT ON THE ROOF

The concrete layout and number of snow catchers depends on the roof slope, its size and expected load of the snow layer.

sklon střechy do 30°



DESCRIPTION

A prefabricated fitting for catching of the snow-layer and prevention of its sliding from the roof construction where the main waterproofing layer is made from a PVC foil and the roof slope does not exceed 30°.

The snow catcher is made from two parts of VIPLANYL® plastic-coated sheet which are welded into one piece. The resulting shape works as a snow catcher.

The bottom part of the square shape is used for fixing of the snow catcher to the structural base and in the corners it has openings with a diameter of 6.2 mm. At the same time it enables watertight connection to the main waterproofing layer by means of overlapping and hot-air welding on the face of the bottom part with a PVC-P layer.

The top part is in the shape of an open side pocket into which the snow is caught. This pocket has an opening in the front part for draining of water and impurities in the roof slope direction.

TECHNICAL DATA

Size of the foil sleeve: 280×280, 330×330 mm

Dimension of the lower part of the snow catcher: 200×200, 250×250 mm

Catchment area of the snow catcher: 35 cm²

Calculation load capacity of snow catcher: 1,3 kN Required load capacity of one anchoring element: 1,2 kN

COLOUR VERSIONS

VIPLANYL 700	VIPLANYL 701	VIPLANYL 707	VIPLANYL 712	VIPLANYL 720
RAL 9016	RAL 9018	RAL 7035	RAL 7040	RAL 7012
VIPLANYL 740	VIPLANYL 760	VIPLANYL 460	VIPLANYL 480	VIPLANYL 860
RAL 7015	RAL 9004	RAL 3016	RAL 8004	RAL 8017